

Object	Property or Method	Meaning
document	createElement(n)	Make a new Element object of type n.
	createTextNode(t)	Make a new text node with the text t.
	getElementsByTagName(n)	Find all the Element objects of type n in the document and return them in a NodeList.
Element	getAttribute(n)	Return the string value of this element's attribute with name n.
	setAttribute(n, v)	Set the value of this element's attribute with name n to v.
	getElementsByTagName(n)	Find all the Element objects of type n in this element's children and return them in a NodeList.
	appendChild(e)	Add the Element e to this element's children after all its existing children.
	insertBefore(e, c)	Add the Element e to this element's children, before the child c.
	removeChild(c)	Remove the Element c from among this element's children.
	replaceChild(c, d)	Replace the Element's child d with c.
	firstChild	This element's first child Element.
	lastChild	This element's last child Element.
	previousSibling	The Element to the left of this element in the tree.
	nextSibling	The Element to the right of this element in the tree.
	parentNode	The Element above this element in the tree.
	childNodes	A NodeList containing all this element's children.
	nodeType	Always equal to 1.
NodeList	item(i)	Get the object at position i in the list.
	length	The number of items in the list.
Text	data	The string of text.
	length	The number of characters in the text.
	nodeType	Always equal to 3.

Principal DOM objects